

**RUBBER COMPOSITION AND CURED PRODUCT**

Patent Number: JP4154855  
Publication date: 1992-05-27  
Inventor(s): NAKAMURA TSUTOMU  
Applicant(s): SHIN ETSU CHEM CO LTD  
Requested Patent: 特 許 JP4154855  
Application Number: JP19900280844 19901019  
Priority Number(s):  
IPC Classification: C08L23/16 ; C08G77/442 ; C08K3/08 ; C08K3/10 ; C08L83/05  
EC Classification:  
Equivalents: JP1930038C, JP6062820B

**Abstract**

**PURPOSE:** To obtain a rubber composition, excellent in heat resistance and vulcanizable with hot air by blending an ethylene-propylene-diene copolymer with a specific organohydrogenpolysiloxane and platinum (compound).  
**CONSTITUTION:** The objective composition is obtained by blending (A) an ethylene-propylene-diene copolymer (preferably with 40-60wt.% propylene content) alone or a mixture, composed of  $\geq 60$ wt.% ethylene-propylene-diene copolymer and  $\leq 40$ wt.% organopolysiloxane without containing any hydrogen atom bound to silicon atom, with (B) an organohydrogenpolysiloxane having  $\geq 2$  hydrogen atoms bound to silicon atom in one molecule and (C) platinum or a compound thereof. The aforementioned composition can be vulcanized by a conventional method; however, vulcanization with hot air can especially be carried out. Thereby, a cured rubber product excellent in elasticity can be obtained by heat treatment at 150-200 deg.C for 5-10min.

Data supplied from the esp@cenet database - I2